



customised equipment, **AccuTEC** offers Distributors and Customers all the possibilities to meet their price, technology and performance requirements.

From the very beginning, **AccuTEC** has placed the highest priority on creating products and services that provide maximum value to its Customers. The continuous growth in **AccuTEC** along its history reflects the acceptance of our products and the confidence of our Customers. Currently, **AccuTEC** scales are exported to different continents worldwide. **AccuTEC** distinguishes itself from the competition by producing scales with high quality and reasonable pricing. From standard products to sophisticated

UWA Weighing Series

- High accuracy up to 1/30,000 resolution
- Rugged design with overload protector
- Large LCD with backlight display
- Long life rechargeable battery 160 hrs
- Hi-Lo check-weighing function available
- Auto zero tracking and tare
- 285 x 240 mm Stainless Steel Weighing Pan



Specifications:-

- UWA-B: 3Kg x 0.2g, 6Kg x 0.5g, 12Kg x 1g and 30Kg x 2g
UWA-C: 3Kg x 0.1g, 6Kg x 0.2g, 15Kg x 0.5g and 30Kg x 1

UCA Counting Series

- High accuracy up to 1/30,000 resolution
- Rugged design with overload protector
- Large LCD with backlight display
- Long life rechargeable battery 160 hrs
- Hi-Lo check-weighing function available
- Auto zero tracking and tare
- 285 x 240 mm Stainless Steel Weighing Pan



Specifications:-

- UCA-B: 3Kg x 0.2g, 6Kg x 0.5g, 12 Kg x 1g and 30Kg x 2g
UCA-C: 3Kg x 0.1g, 6Kg x 0.2g, 15Kg x 0.5g and 30Kg x 1

BSWC-B-PF Weighing Series

- High accuracy up to 1/15,000 resolution
- Rugged design with overload protector
- Large LED with backlight display
- Long life rechargeable battery 90 hrs
- Auto zero tracking and tare
- 380 x 480 mm stainless steel weighing pan
- Adjustable leveling with four stands



Specifications:-

- BSWC-B-PF-60: 60Kg x 5g, 60Kg x 10g
BSWC-B-PF-150: 150Kg x 10g, 150Kg x 20g
BSWC-B-PF-300: 300Kg x 20g, 300Kg x 50g

BSC-B-PF Counting Series

- High accuracy up to 1/15,000, resolution
- Rugged design with overload protector
- Large LCD with backlight display
- Long life rechargeable battery 160 hrs
- Hi-Lo check-weighing function available
- Auto zero tracking and tare
- 380 x 480 mm stainless steel weighing pan
- Adjustable leveling with four stands



Specifications:-

- BSC-B-PF-60: 60Kg x 5g, 60Kg x 10g
BSC-B-PF-150: 150Kg x 10g, 150Kg x 20g
BSC-B-PF-300: 300Kg x 20g, 300Kg x 50g

BSW-S-PF Waterproof Series

- All Stainless steel construction
- Stainless steel load cell and indicator
- 400 x 500 mm stainless steel weighing pan
- 20mm Bright green LED display
- Direct AC/DC power
- Kg and pound conversion
- Weighing and easy counting function
- Auto Zero-tracking, tare and memory



Specifications:-

- BSW-S-60: 60Kg x 10g
BSW-S-150: 150Kg x 20g
BSW-S-300: 300Kg x 50g

UT Crane Scale Series

- Initial Range: Up to 100% loadcell output
- Tare Range: 100% of scale capacity
- Auto zero tracking
- Kg / lb conversion
- 1 inch bright & large LED display
- Overload indication
- Long life rechargeable battery 100-120 hrs
- Auto power off




Specifications:-

- UT-1-010: 1,000Kg x 0.5Kg
UT-1-020: 2,000 Kg x 1Kg
UT-1-030: 3,000 Kg x 1Kg

FS Floor Scale Series

- High accuracy indicator up to 1/15,000 resolution
- Rugged design with overload protector
- Large LCD with backlight display
- Long life rechargeable battery 160 hrs
- Hi-Lo and dynamic weighing
- Auto zero tracking and tare
- Auto power off
- Powder coated surface and thicker platform plate (ramp is optional)



Specifications:-

- FS-001: 1,000Kg x 0.5Kg (platform size: 1 m x 1 m)
FS-002: 2,000Kg x 0.5Kg (platform size: 1.2 m x 1.2 m)
FS-003: 3,000Kg x 1Kg (platform size: 1.5 m x 1.5 m)

ULP Thermal Printer Series

(compatible to selected model only)

- Small, lightweight and installable in a narrow area
- High speed and low noise
- Long-life printing head and high reliability
- With bar code print out
- Could store up to 99 memories



Specifications:-

- Printing Speed: 50mm/s
Paper Size: 57mm×25mm / 57mm×43mm / 57mm×75mm
Print Head Life: Up to 70Km print out
Interface: RS-232
Power: 12VDC / 2.5A